



ECO-STÜTZENKLEBSTOFF

This safety data sheet was created pursuant to the requirements of:
Regulation (EC) No. 1907/2006 and Regulation (EC) No. 1272/2008

This SDS is for generic information purposes and does not reflect required country specific information for OEL

Tate Global GmbH

Zum Stadion 4, 63808 Haibach, Germany

T: +49 (0) 6021 63949-0 E: infoDE@tateglobal.com W: [tateglobal.com/de](https://www.tateglobal.com/de)

© 2025 Tate Global GmbH
We reserve the right to change specification or design and supply products which may differ from those described and illustrated without notice and without liability.
[tate-eco-stützenklebstoff-safety-datasheet-en-de-v2 4/2025](#)



ECO-STÜTZENKLEBSTOFF

This safety data sheet was created pursuant to the requirements of: Regulation (EC) No. 1907/2006 and Regulation (EC) No. 1272/2008 This SDS is for generic information purposes and does not reflect required country specific information for OEL

SECTION 1: Identification of the substance/mixture and of the company/undertaking

Page 1

- 1.1 Product identifier
- 1.2 Relevant identified uses of the substance or mixture and uses advised against
- 1.3 Details of the supplier of the safety data sheet
- 1.4 Emergency telephone number
- 1.5 Emergency Telephone

SECTION 2: Hazards identification

Page 1

- 2.1 Classification of the substance or mixture Regulation (EC) No 1272/2008
- 2.2 Label elements
- 2.3 Other hazards

SECTION 3: Composition/information on ingredients

Page 2

- 3.1 Substances
- 3.2 Mixtures

SECTION 4: First aid measures

Page 3

- 4.1 Description of first aid measures
- 4.2. Most important symptoms and effects, both acute and delayed
- 4.3. Indication of any immediate medical attention and special treatment needed

SECTION 5: Firefighting measures

Page 3

- 5.1 Extinguishing media
- 5.2 Special hazards arising from the substance or mixture
- 5.3 Advice for firefighters

SECTION 6: Accidental release measures

Page 4

- 6.1 Personal precautions, protective equipment and emergency procedures
- 6.2 Environmental Precautions
- 6.3 Methods and material for containment and cleaning up
- 6.4 Reference to other sections

SECTION 7: Handling and storage

Page 4

- 7.1 Precautions for safe handling
- 7.2 Conditions for safe storage, including any incompatibilities
- 7.3 Specific end use(s)

SECTION 8: Exposure controls/personal protection

Page 5

- 8.1 Control parameters
- 8.2 Exposure controls

SECTION 9: Physical and chemical properties

Page 8

- 9.2 Other information Solid content (%)
- 9.2.1 Information with regards to physical hazard classes Not applicable
- 9.2.2 Other safety characteristics

SECTION 10: Stability and reactivity

Page 8

- 10.1 Reactivity
- 10.2 Chemical stability
- 10.3 Possibility of hazardous reactions
- 10.4 Conditions to avoid
- 10.5 Incompatible materials
- 10.6 Hazardous decomposition products

Tate Global GmbH

Zum Stadion 4, 63808 Haibach, Germany
T: +49 (0) 6021 63949-0 E: infoDE@tateglobal.com W: tateglobal.com/de

© 2025 Tate Global GmbH
We reserve the right to change specification or design and supply products which may differ from those described and illustrated without notice and without liability.
tate-eco-stützenklebstoff-safety-datasheet-en-de-v2 4/2025

Tate.[®]

ECO-STÜTZENKLEBSTOFF

This safety data sheet was created pursuant to the requirements of: Regulation (EC) No. 1907/2006 and Regulation (EC) No. 1272/2008 This SDS is for generic information purposes and does not reflect required country specific information for OEL

SECTION 11: Toxicological information

Page 11

- 11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008
- 11.2 Information on other hazards
 - 11.2.1 Endocrine disrupting properties
 - 11.2.2 Other information

SECTION 12: Ecological information

Page 12

- 12.1 Toxicity
- 12.2 Persistence and degradability
- 12.3 Bioaccumulative potential
- 12.4 Mobility in soil
- 12.5 Results of PBT and vPvB assessment
- 12.6 Endocrine disrupting properties
- 12.7 Other adverse effects

SECTION 13: Disposal considerations

Page 13

- 13.1 Waste treatment methods

SECTION 14: Transport information

Page 13

- 14.1 UN number or ID number
- 14.2 Proper Shipping Name
- 14.3 Transport hazard class(es)
- 14.4 Packing group
- 14.5 Environmental hazards
- 14.6 Special Provisions
- 14.7 Maritime transport in bulk according to IMO instruments
- 14.3 Transport hazard class(es)
- 14.4 Packing group
- 14.5 Environmental hazards
- 14.6 Special Provisions

Section 15: REGULATORY INFORMATION

Page 14

- 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture
- 15.2 Chemical safety assessment

SECTION 16: Other information

Page 15

Tate Global GmbH

Zum Stadion 4, 63808 Haibach, Germany
T: +49 (0) 6021 63949-0 E: infoDE@tateglobal.com W: tateglobal.com/de

© 2025 Tate Global GmbH
We reserve the right to change specification or design and supply products which may differ from those described and illustrated without notice and without liability.
tate-eco-stützenklebstoff-safety-datasheet-en-de-v2 4/2025

Tate.[®]

ECO-STÜTZENKLEBSTOFF

This safety data sheet was created pursuant to the requirements of: Regulation (EC) No. 1907/2006 and Regulation (EC) No. 1272/2008 This SDS is for generic information purposes and does not reflect required country specific information for OEL

1

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product Name Form

Other means of identification Pure substance/mixture

This substance/ mixture contains nanoforms

Mixture

1.2. Relevant identified uses of the substance or mixture and uses advised against

Recommended use Uses	Adhesive
advised against	None known.

1.3. Details of the supplier of the safety data sheet

Company Name

Bostik GmbH
An der Bundesstrasse 16
33829 Borgholzhausen, Germany
Tel: +49 (0) 5425 / 801 0
Fax: +49 (0) 5425 / 801 140

E-mail address

1.4. Emergency telephone number

1.5. Emergency Telephone 112

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Regulation (EC) No 1272/2008

This mixture is classified as not hazardous according to regulation (EC) 1272/2008 [CLP]

2.2. Label elements

This mixture is classified as not hazardous according to regulation (EC) 1272/2008 [CLP]

Hazard statements

This mixture is classified as not hazardous according to regulation (EC) 1272/2008 [CLP]

EU Specific Hazard Statements

EUH208 - Contains Trimethoxyvinylsilane. May produce an allergic reaction EUH210 - Safety data sheet available on request

2.3. Other hazards

Small amounts of methanol (CAS 67-56-1) are formed by hydrolysis and released upon curing.

PBT & vPvB

This mixture contains no substance considered to be persistent, bioaccumulating or toxic (PBT). This mixture contains no substance considered to be very persistent nor very bioaccumulating (vPvB).

Endocrine Disruptor Information This product does not contain any known or suspected endocrine disruptors.

SECTION 3: Composition/information on ingredients

Tate Global GmbH

Zum Stadion 4, 63808 Haibach, Germany
T: +49 (0) 6021 63949-0 E: infoDE@tateglobal.com W: tateglobal.com/de

© 2025 Tate Global GmbH
We reserve the right to change specification or design and supply products which may differ from those described and illustrated without notice and without liability.
tate-eco-stützenklebstoff-safety-datasheet-en-de-v2 4/2025

Tate®

ECO-STÜTZENKLEBSTOFF

This safety data sheet was created pursuant to the requirements of: Regulation (EC) No. 1907/2006 and Regulation (EC) No. 1272/2008 This SDS is for generic information purposes and does not reflect required country specific information for OEL

2

3.1 Substances

Not applicable

3.2 Mixtures

Chemical name	EC No (EU Index No).	CAS No.	Classification according to Regulation (EC) No. 1272/2008 [CLP]	Specific concentration limit (SCL)	M-Factor	M-Factor (long-term)	REACH registration number
Trimethoxyvinylsilane 1 - <2.5 %	(014-049-00-0) 220-449-8	2768-02-7	Skin Sens. 1B (H317) Acute Tox. 4 (H332) Flam. Liq. 3 (H226)	-	-	-	1-2119513215-52-XXXX
Diocetyl tin oxide 0.1 - <0.5 %	212-791-1	870-08-6	STOT SE 2 (H371)	-	-	-	1-2119971268-27-xxxx
Bis(2,2,6,6-tetramethyl-4-piperidyl) sebacate 0.1 - <0.3 %	258-207-9	52829-07-9	Eye Dam. 1 (H318) Repr. 2 (H361f) Aquatic Acute 1 (H400) Aquatic Chronic 2 (H411)	-	-	-	1-2119537297-32-XXXX
Ethyl silicate 0.1 - <0.3 %	(014-005-00-0) 201-083-8	78-10-4	Acute Tox. 4 (H332) Eye Irrit. 2 (H319) STOT SE 3 (H335) Flam. Liq. 3 (H226)	-	-	-	1-2119496195-28-xxxx

Air contaminants formed when using the substance or mixture as intended

Chemical name	EC No (EU Index No)	Weight-%	Classification according to Regulation (EC) No. 1272/2008 [CLP]	Specific concentration limit (SCL)	M-Factor	M-Factor (long-term)	REACH registration number
Methyl alcohol 67-56-1	(603-001-00-X) 200-659-6	1 - <2.5	Acute Tox. 3 (H301) Acute Tox. 3 (H311) Acute Tox. 3 (H331) STOT SE 1 (H370) Flam. Liq. 2 (H225)	STOT SE 1 :: C ₅₀ ≥10% STOT SE 2 :: 3%≤C<10%	-	-	1-211943330 2-44-XXXX

Full text of H- and EUH-phrases: see section 16

Acute Toxicity Estimate

If LD50/LC50 data is not available or does not correspond to the classification category, then the appropriate conversion value from CLP Annex I, Table 3.1.2, is used to calculate the acute toxicity estimate (ATEmix) for classifying a mixture based on its components

Chemical name	EC No (EU Index No)	CAS No	Oral LD50 mg/kg	Dermal LD50 mg/kg	Inhalation LC50 - 4 hour - dust/mist - mg/L	Inhalation LC50 - 4 hour - vapour - mg/L	Inhalation LC50 - 4 hour - gas - ppm
Trimethoxyvinylsilane	(014-049-00-0) 220-449-8	2768-02-7	-	-	-	11	-
Diocetyl tin oxide	212-791-1	870-08-6	-	-	-	-	-
Bis(2,2,6,6-tetramethyl-4-piperidyl) sebacate	258-207-9	52829-07-9	-	-	-	-	-
Ethyl silicate	(014-005-00-0) 201-083-8	78-10-4	-	-	4.9	11	-

This product does not contain candidate substances of very high concern at a concentration ≥0.1% (Regulation (EC) No. 1907/2006 (REACH), Article 59)

SECTION 4: First aid measures

Tate Global GmbH

Zum Stadion 4, 63808 Haibach, Germany

T: +49 (0) 6021 63949-0 E: infoDE@tateglobal.com W: tateglobal.com/de

© 2025 Tate Global GmbH
We reserve the right to change specification or design and supply products which may differ from those described and illustrated without notice and without liability.
tate-eco-stützenklebstoff-safety-datasheet-en-de-v2 4/2025

Tate®

ECO-STÜTZENKLEBSTOFF

This safety data sheet was created pursuant to the requirements of: Regulation (EC) No. 1907/2006 and Regulation (EC) No. 1272/2008 This SDS is for generic information purposes and does not reflect required country specific information for OEL

4.1. Description of first aid measures

General advice	If medical advice is needed, have product container or label at hand. Remove to fresh air.
Inhalation Eye contact	If symptoms persist, call a doctor.
Skin contact	Immediately flush with plenty of water. After initial flushing, remove any contact lenses and continue flushing for at least 15 minutes. Consult an ophthalmologist.
Ingestion	Wash off immediately with soap and plenty of water. In the case of skin irritation or allergic reactions see a doctor.
Self-protection of the first aider	Do NOT induce vomiting. Rinse mouth thoroughly with water. Never give anything by mouth to an unconscious person. Call a doctor or poison control centre immediately. Small amounts of toxic methanol are released by hydrolysis.

4.2. Most important symptoms and effects, both acute and delayed

Symptoms	None known.
-----------------	-------------

4.3. Indication of any immediate medical attention and special treatment needed

Note to doctors upon curing.	Treat symptomatically. Small amounts of methanol (CAS 67-56-1) are formed by hydrolysis and released
--	--

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable Extinguishing Media	Water spray, carbon dioxide (CO ₂), dry chemical, alcohol-resistant foam.
Unsuitable extinguishing media	Full water jet.

5.2. Special hazards arising from the substance or mixture

Specific hazards arising from the chemical	Thermal decomposition can lead to release of irritating gases and vapours.
Hazardous combustion products	Carbon monoxide. Carbon dioxide (CO ₂).

5.3. Advice for firefighters

Special protective equipment and precautions for fire-fighters	Wear self contained breathing apparatus for fire fighting if necessary.
---	---

Tate Global GmbH

Zum Stadion 4, 63808 Haibach, Germany

T: +49 (0) 6021 63949-0 E: infoDE@tateglobal.com W: tateglobal.com/de

© 2025 Tate Global GmbH

We reserve the right to change specification or design and supply products which may differ from those described and illustrated without notice and without liability.
tate-eco-stützenklebstoff-safety-datasheet-en-de-v2 4/2025

Tate®

SECTION 6: Accidental release measures**6.1. Personal precautions, protective equipment and emergency procedures**

Personal precautions Ensure adequate ventilation. Use personal protective equipment as required. Do not get in eyes, on skin, or on clothing.

For emergency responders Use personal protection recommended in Section 8.

6.2 Environmental Precautions Prevent product from entering drains. Do not allow to enter into soil/subsoil. See Section 12 for additional Ecological Information.

6.3. Methods and material for containment and cleaning up

Methods for containment Use a non-combustible material like vermiculite, sand or earth to soak up the product and place into a container for later disposal.

Methods for cleaning up Take up mechanically, placing in appropriate containers for disposal.

Prevention of secondary hazards Clean contaminated objects and areas thoroughly observing environmental regulations.

6.4. Reference to other sections

Reference to other sections See section 8 for more information. See section 13 for more information.

SECTION 7: Handling and storage**7.1. Precautions for safe handling**

Advice on safe handling Ensure adequate ventilation. Use personal protective equipment as required. Avoid contact with skin, eyes or clothing.

General hygiene considerations Do not eat, drink or smoke when using this product. Wash hands before breaks and after work. Take off contaminated clothing and wash it before reuse.

7.2. Conditions for safe storage, including any incompatibilities

Storage Conditions Protect from moisture. Keep containers tightly closed in a dry, cool and well-ventilated place. Keep away from food, drink and animal feedingstuffs.

Recommended storage temperature Keep at temperatures between 10 and 35 °C.

7.3. Specific end use(s)

Specific use(s)
Adhesive.

Risk Management Methods (RMM) The information required is contained in this Safety Data Sheet.

Other information Observe technical data sheet.

Tate Global GmbH

Zum Stadion 4, 63808 Haibach, Germany
T: +49 (0) 6021 63949-0 E: infoDE@tateglobal.com W: tateglobal.com/de

© 2025 Tate Global GmbH
We reserve the right to change specification or design and supply products which may differ from those described and illustrated without notice and without liability.
tate-eco-stützenklebstoff-safety-datasheet-en-de-v2 4/2025

The logo for Tate, featuring the word "Tate" in a bold, blue, sans-serif font, followed by a registered trademark symbol (®).

SECTION 8: Exposure controls/personal protection**8.1. Control parameters**

Exposure Limits Small amounts of methanol (CAS 67-56-1) are formed by hydrolysis and released upon curing

Only European Community Occupational Exposure Limits will be shown in this document. Please refer to regional SDS for further information.

Chemical name	European Union
Methyl alcohol 67-56-1	TWA: 200 ppm TWA: 260 mg/m ³ *
Ethyl silicate 78-10-4	TWA: 44 mg/m ³ TWA: 5 ppm

Derived No Effect Level (DNEL) No information available

Derived No Effect Level (DNEL)			
Trimethoxyvinylsilane (2768-02-7)			
Type	Exposure route	Derived No Effect Level (DNEL)	Safety factor
worker Systemic health effects Long term	Inhalation	27,6 mg/m ³	
worker Systemic health effects Long term	Dermal	3,9 mg/kg bw/d	

Dioctyltin oxide (870-08-6)			
Type	Exposure route	Derived No Effect Level (DNEL)	Safety factor
worker Long term Systemic health effects	Dermal	0.05 mg/kg bw/d	
worker Long term Systemic health effects	Inhalation	0.004 mg/m ³	

Bis(2,2,6,6-tetramethyl-4-piperidyl) sebacate (52829-07-9)			
Type	Exposure route	Derived No Effect Level (DNEL)	Safety factor
worker Short term Long term Systemic health effects	Inhalation	2.82 mg/m ³	
worker Long term Systemic health effects	Dermal	1.6 mg/kg	

Ethyl silicate (78-10-4)			
Type	Exposure route	Derived No Effect Level (DNEL)	Safety factor
worker Short term Systemic health effects	Dermal	12.1 mg/kg bw/d	
worker Systemic health effects Long term	Dermal	12.1 mg/kg bw/d	

Tate Global GmbH

Zum Stadion 4, 63808 Haibach, Germany

T: +49 (0) 6021 63949-0 E: infoDE@tateglobal.com W: tateglobal.com/de

ECO-STÜTZENKLEBSTOFF

This safety data sheet was created pursuant to the requirements of: Regulation (EC) No. 1907/2006 and Regulation (EC) No. 1272/2008 This SDS is for generic information purposes and does not reflect required country specific information for OEL

6

worker Short term Systemic health effects	Inhalation	85 mg/m ³	
worker Short term Local health effects	Inhalation	85 mg/m ³	
worker Long term Systemic health effects	Inhalation	85 mg/m ³	
worker Long term Local health effects	Inhalation	85 mg/m ³	

Derived No Effect Level (DNEL)			
Trimethoxyvinylsilane (2768-02-7)			
Type	Exposure route	Derived No Effect Level (DNEL)	Safety factor
Consumer Systemic health effects Long term	Inhalation	18,9 mg/m ³	
Consumer Systemic health effects Long term	Dermal	7,8 mg/kg bw/d	
Consumer Systemic health effects Long term	Oral	0,3 mg/kg bw/d	

Dioctyltin oxide (870-08-6)			
Type	Exposure route	Derived No Effect Level (DNEL)	Safety factor
Consumer Long term Systemic health effects	Oral	0.0005 mg/kg bw/d	
Consumer Long term Systemic health effects	Dermal	0.025 mg/kg bw/d	
Consumer Long term Systemic health effects	Inhalation	0.0009 mg/m ³	

Bis(2,2,6,6-tetramethyl-4-piperidyl) sebacate (52829-07-9)			
Type	Exposure route	Derived No Effect Level (DNEL)	Safety factor
Consumer Long term Systemic health effects	Dermal	0.8 mg/kg	
Consumer Long term Systemic health effects	Oral	0.4 mg/kg	

Ethyl silicate (78-10-4)			
Type	Exposure route	Derived No Effect Level (DNEL)	Safety factor
Consumer Short term Systemic health effects	Dermal	8.4 mg/kg bw/d	
Consumer Long term Systemic health effects	Dermal	8.4 mg/kg bw/d	

Tate Global GmbH

Zum Stadion 4, 63808 Haibach, Germany

T: +49 (0) 6021 63949-0 E: infoDE@tateglobal.com W: tateglobal.com/de

© 2025 Tate Global GmbH
We reserve the right to change specification or design and supply products which may differ from those described and illustrated without notice and without liability.
tate-eco-stützenklebstoff-safety-datasheet-en-de-v2 4/2025

Tate.[®]

ECO-STÜTZENKLEBSTOFF

This safety data sheet was created pursuant to the requirements of: Regulation (EC) No. 1907/2006 and Regulation (EC) No. 1272/2008 This SDS is for generic information purposes and does not reflect required country specific information for OEL

7

Consumer Short term Systemic health effects	Inhalation	25 mg/m³	
Consumer Short term Local health effects	Inhalation	25 mg/m³	
Consumer Long term Systemic health effects	Inhalation	25 mg/m³	
Consumer Long term Local health effects	Inhalation	25 mg/m³	

Predicted No Effect Concentration (PNEC)

Predicted No Effect Concentration (PNEC)	
Trimethoxyvinylsilane (2768-02-7)	
Environmental compartment	Predicted No Effect Concentration (PNEC)
Freshwater	0.34 mg/l
Marine water	0.034 mg/l
Microorganisms in sewage treatment	110 mg/l

Diocetyl tin oxide (870-08-6)	
Environmental compartment	Predicted No Effect Concentration (PNEC)
Freshwater sediment	0.02798 mg/kg dry weight
Marine sediment	0.002798 mg/kg dry weight
Microorganisms in sewage treatment	100 mg/l

Bis(2,2,6,6-tetramethyl-4-piperidyl) sebacate (52829-07-9)	
Environmental compartment	Predicted No Effect Concentration (PNEC)
Freshwater	0.018 mg/l
Marine water	0.0018 mg/l
Freshwater sediment	29 mg/kg
Marine sediment	2.9 mg/kg
Soil	5.9 mg/kg

Ethyl silicate (78-10-4)	
Environmental compartment	Predicted No Effect Concentration (PNEC)
Freshwater	0.192 mg/l
Marine water	0.0192 mg/l
Freshwater sediment	0.18 mg/kg dry weight
Marine sediment	0.018 mg/kg dry weight
Soil	0.05 mg/kg

8.2 Exposure controls

Engineering controls

Personal protective equipment Eye/face protection

Hand protection Wear suitable gloves

Skin and body protection

Respiratory protection

Recommended filter type:

Ensure adequate ventilation, especially in confined areas.

Wear safety glasses with side shields (or goggles). Eye protection must conform to standard EN 166.

Recommended Use: Nitrile rubber. Butyl rubber. Glove thickness > 0.4 mm. Ensure that the breakthrough time of the glove material is not exceeded. Refer to glove supplier for information on breakthrough time for specific gloves. The breakthrough time for the mentioned glove material is in general greater than 480 min. Gloves must conform to standard EN 374

Tate Global GmbH

Zum Stadion 4, 63808 Haibach, Germany

T: +49 (0) 6021 63949-0 E: infoDE@tateglobal.com W: tateglobal.com/de

© 2025 Tate Global GmbH
We reserve the right to change specification or design and supply products which may differ from those described and illustrated without notice and without liability.
tate-eco-stützenklebstoff-safety-datasheet-en-de-v2 4/2025

Tate.[®]

ECO-STÜTZENKLEBSTOFF

This safety data sheet was created pursuant to the requirements of: Regulation (EC) No. 1907/2006 and Regulation (EC) No. 1272/2008 This SDS is for generic information purposes and does not reflect required country specific information for OEL

8

Wear suitable protective clothing.

Wear a respirator conforming to EN 140 with Type A/P2 filter or better.

In case of inadequate ventilation wear respiratory protection.

Organic gases and vapours filter conforming to EN 14387. White. Brown.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state	Liquid Paste
Appearance Colour	White to Beige Characteristic.
Odour	No information available
Odour threshold	

Property	Values	Remarks • Method
Melting point / freezing point Initial boiling point and boiling range	No data available No data available	
Flammability Flammability Limit in Air	Not applicable for liquids .	
Upper flammability or explosive limits	No data available	None known
Lower flammability or explosive limits	No data available	
Flash point	> 63 °C	CC (closed cup) None known
Autoignition temperature	No data available	Not applicable. Reacts with water.
Decomposition temperature pH (as aqueous solution) Kinematic viscosity Dynamic viscosity	.	
Water solubility	No data available	
Solubility(ies)	No data available	
Partition coefficient Vapour pressure	Reacts with water. Product cures with moisture	
Relative density Bulk Density	No data available	
Liquid Density	No data available	
Relative vapour density Particle characteristics	No data available	
	1.3 - 1.5	
Particle Size	No data available	
Particle Size Distribution	No information available	

9.2. Other information

No information available

Solid content (%)

VOC content

No data available

9.2.1. Information with regards to physical hazard classes Not applicable

9.2.2. Other safety characteristics

No information available

SECTION 10: Stability and reactivity

10.1. Reactivity

Reactivity	Product cures with moisture.
------------	------------------------------

10.2. Chemical stability

Tate Global GmbH

Zum Stadion 4, 63808 Haibach, Germany

T: +49 (0) 6021 63949-0 E: infoDE@tateglobal.com W: tateglobal.com/de

© 2025 Tate Global GmbH
We reserve the right to change specification or design and supply products which may differ from those described and illustrated without notice and without liability.
tate-eco-stützenklebstoff-safety-datasheet-en-de-v2 4/2025

Tate.[®]

ECO-STÜTZENKLEBSTOFF

This safety data sheet was created pursuant to the requirements of: Regulation (EC) No. 1907/2006 and Regulation (EC) No. 1272/2008 This SDS is for generic information purposes and does not reflect required country specific information for OEL

9

Stability Stable under normal conditions.

Explosion data

Sensitivity to mechanical impact None.

Sensitivity to static discharge None.

10.3. Possibility of hazardous reactions

Possibility of hazardous reactions None under normal processing.

10.4 Conditions to avoid

Conditions to avoid Protect from moisture. Product cures with moisture.

10.5. Incompatible materials

Incompatible materials None known based on the information supplied.

10.6. Hazardous decomposition products

Hazardous decomposition products None under normal use conditions. Small amounts of methanol (CAS 67-56-1) are formed by hydrolysis and released upon curing.

SECTION 11: Toxicological information

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Information on likely routes of exposure

Product Information

Inhalation Based on available data, the classification criteria are not met. Based on available data, the classification criteria are not met. Based on available data, the classification criteria are not met.

Eye contact Based on available data, the classification criteria are not met. Based on available data, the classification criteria are not met. Based on available data, the classification criteria are not met.

Skin contact Based on available data, the classification criteria are not met. Based on available data, the classification criteria are not met. Based on available data, the classification criteria are not met.

Ingestion

Symptoms related to the physical, chemical and toxicological characteristics

Symptoms No information available.

Acute toxicity

Numerical measures of toxicity

The following values are calculated based on chapter 3.1 of the GHS document

ATEmix (dermal) 19,057.10 mg/kg

ATEmix (inhalation-vapour) 1,171.70 mg/l

Component Information

Chemical name	Oral LD50	Dermal LD50	Inhalation LC50
Trimethoxyvinylsilane	LD50 = 7120 -7236 mg/kg (Rattus) OECD 401	= 3540 mg/kg (Oryctolagus cuniculus)	LC50 (4hr) 16.8 mg/l (Rattus) OECD TG 403
Dioctyltin oxide	=2500 mg/kg (Rattus)	LD50 > 2000 mg/kg (Rattus) OECD 402	-

Tate Global GmbH

Zum Stadion 4, 63808 Haibach, Germany

T: +49 (0) 6021 63949-0 E: infoDE@tateglobal.com W: tateglobal.com/de

© 2025 Tate Global GmbH
We reserve the right to change specification or design and supply products which may differ from those described and illustrated without notice and without liability.
tate-eco-stützenklebstoff-safety-datasheet-en-de-v2 4/2025

Tate.[®]

ECO-STÜTZENKLEBSTOFF

This safety data sheet was created pursuant to the requirements of: Regulation (EC) No. 1907/2006 and Regulation (EC) No. 1272/2008 This SDS is for generic information purposes and does not reflect required country specific information for OEL

10

Bis(2,2,6,6-tetramethyl-4-piperidyl) sebacate	LD50 (Rattus) > 2000 mg/kg OECD 423	LD50 (Rattus) > 3 170 mg/kg OECD 402	=500 mg/m ³ (Rattus) 4 h
Ethyl silicate	LD50 > 2500 mg/kg (Rattus) OECD 423	= 5878 mg/kg (Oryctolagus cuniculus) = 6300 µL/kg (Oryctolagus cuniculus)	= 10 mg/L (Rat male) 4 h > 16.8 mg/L (Rat female) 4 h

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Skin corrosion/irritation

Based on available data, the classification criteria are not met.

Trimethoxyvinylsilane (2768-02-7)

Method	Species	Exposure route	Effective dose	Exposure time	Results
	Rabbit	Dermal	0.5 mL	24 hours	Non-irritant

Bis(2,2,6,6-tetramethyl-4-piperidyl) sebacate (52829-07-9)

Method	Species	Exposure route	Effective dose	Exposure time	Results
OECD Test No. 404: Acute Dermal Irritation/Corrosion	Rabbit	Dermal			Non-irritant

Serious eye damage/eye irritation

Based on available data, the classification criteria are not met.

Trimethoxyvinylsilane (2768-02-7)

Method	Species	Exposure route	Effective dose	Exposure time	Results
OECD Test No. 405: Acute Eye Irritation/ Corrosion	Rabbit	eye		24 hours	Non-irritant

Bis(2,2,6,6-tetramethyl-4-piperidyl) sebacate (52829-07-9)

Method	Species	Exposure route	Effective dose	Exposure time	Results
OECD Test No. 405: Acute Eye Irritation/ Corrosion	Rabbit	eye			Eye Damage

Respiratory or skin sensitisation

May produce an allergic reaction. OECD Test No. 406: Skin Sensitisation. No sensitisation responses were observed. No classification is proposed, based on conclusive negative data.

Method	Species	Exposure route	Results
OECD Test No. 406: Skin Sensitisation	Guinea pig	Dermal	No sensitisation responses were observed

Trimethoxyvinylsilane (2768-02-7)

Method	Species	Exposure route	Results
OECD Test No. 406: Skin Sensitisation, Buehler test	Guinea pig	Dermal	sensitising

Bis(2,2,6,6-tetramethyl-4-piperidyl) sebacate (52829-07-9)

Method	Species	Exposure route	Results
OECD Test No. 406: Skin Sensitisation	Guinea pig		No sensitisation responses were observed

Germ cell mutagenicity

Based on available data, the classification criteria are not met.

Component Information

Trimethoxyvinylsilane (2768-02-7)

Method	Species	Results
OECD Test No. 471: Bacterial Reverse Mutation Test	in vitro	Not mutagenic

Tate Global GmbH

Zum Stadion 4, 63808 Haibach, Germany

T: +49 (0) 6021 63949-0 E: infoDE@tateglobal.com W: tateglobal.com/de

© 2025 Tate Global GmbH
We reserve the right to change specification or design and supply products which may differ from those described and illustrated without notice and without liability.
tate-eco-stützenklebstoff-safety-datasheet-en-de-v2 4/2025

Tate.[®]

ECO-STÜTZENKLEBSTOFF

This safety data sheet was created pursuant to the requirements of: Regulation (EC) No. 1907/2006 and Regulation (EC) No. 1272/2008 This SDS is for generic information purposes and does not reflect required country specific information for OEL

11

Bis(2,2,6,6-tetramethyl-4-piperidyl) sebacate (52829-07-9)

Carcinogenicity Based on available data, the classification criteria are not met.

Reproductive toxicity Based on available data, the classification criteria are not met.

Trimethoxyvinylsilane (2768-02-7)

Method	Species	Results
OECD Test No. 422: Combined Repeated Dose Toxicity Study with the Reproduction/Developmental Toxicity Screening Test	Rat	Not Classifiable

Bis(2,2,6,6-tetramethyl-4-piperidyl) sebacate (52829-07-9)

Method	Species	Results
OECD Test No. 414: Pre-natal Development Toxicity Study	Rat, Rabbit	reproductive toxicant

STOT - single exposure Based on available data, the classification criteria are not met.

Diocetyl tin oxide (870-08-6)

Method	Species	Exposure route	Effective dose	Exposure time	Results
OECD Test No. 422: Combined Repeated Dose Toxicity Study with the Reproduction/Developmental Toxicity Screening Test	Rat	Oral	5 mg/kg	28 days	0.3 - 0.5 mg/kg bw/d May cause damage to the following organs: Immune system

Bis(2,2,6,6-tetramethyl-4-piperidyl) sebacate (52829-07-9)

STOT - repeated exposure Based on available data, the classification criteria are not met.

Trimethoxyvinylsilane (2768-02-7)

Method	Species	Exposure route	Effective dose	Exposure time	Results
OECD Test No. 413: Sub-chronic Inhalation Toxicity: 90-day Study	Rat	Inhalation vapour		90 days	0.058 NOAEL

Diocetyl tin oxide (870-08-6)

Method	Species	Exposure route	Effective dose	Exposure time	Results
	Rat Rabbit			28 days	0.3 -0.5 mg/kg bw/d

Bis(2,2,6,6-tetramethyl-4-piperidyl) sebacate (52829-07-9)

Aspiration hazard Based on available data, the classification criteria are not met.

11.2. Information on other hazards

11.2.1. Endocrine disrupting properties

Endocrine disrupting properties No information available.

11.2.2. Other information

Other adverse effects No information available.

SECTION 12: Ecological information

12.1. Toxicity

Ecotoxicity

Tate Global GmbH

Zum Stadion 4, 63808 Haibach, Germany
T: +49 (0) 6021 63949-0 E: infoDE@tateglobal.com W: tateglobal.com/de

© 2025 Tate Global GmbH
We reserve the right to change specification or design and supply products which may differ from those described and illustrated without notice and without liability.
tate-eco-stützenklebstoff-safety-datasheet-en-de-v2 4/2025

Tate.[®]

ECO-STÜTZENKLEBSTOFF

12

This safety data sheet was created pursuant to the requirements of: Regulation (EC) No. 1907/2006 and Regulation (EC) No. 1272/2008 This SDS is for generic information purposes and does not reflect required country specific information for OEL

Chemical name	Algae/aquatic plants	Fish	Toxicity to microorganisms	Crustacea	M-Factor	M-Factor (long-term)
Trimethoxyvinylsilane 2768-02-7	EC 50 (72h) > 957 mg/l (Desmodesmus subspicatus) EU Method C.3	LC50 (96h) = 191 mg/l (Oncorhynchus mykiss)	-	EC50(48hr) 168.7mg/l (Daphnia magna)		
Diocetyl tin oxide 870-08-6	EC50 (3hr) >1.000 mg/l (bacteria) (Activated Sludge, Respiration Inhibition Test)	LC50 (96hr) >0,09 mg/l (Brachydanio rerio (zebra)) (Acute Toxicity Test)	-	EC50 (48Hr) >0,21 mg/l (Daphnia magna (Daphnia magna)) (Daphnia sp. Acute Immobilisation Test)		
Bis(2,2,6,6-tetramethyl-4-piperidyl) sebacate 52829-07-9	EC50 72Hr 0.705 mg/l (Pseudokirchnerella subcapitata)	LC50 (96h) = 5.29 mg/l (Oryzias latipes)	-	LC50 48Hr 8.58 mg/l (Daphnia magna)		
Ethyl silicate 78-10-4	EC 50 (72h) > 100 mg/L (Pseudokirchnerella subcapitata) OECD 201	LC50 (96h) > 245 mg/L (Danio rerio) EU Method C.1	-	-		

12.2. Persistence and degradability

Persistence and degradability

No information available.

Trimethoxyvinylsilane (2768-02-7)

Method	Exposure time	Value	Results
OECD Test No. 301F: Ready Biodegradability: Manometric Respirometry Test (TG 301 F)	28 days	BOD	51 % Not readily biodegradable

Diocetyl tin oxide (870-08-6)

Method	Exposure time	Value	Results
OECD Test No. 301F: Ready Biodegradability: Manometric Respirometry Test (TG 301 F)	755 hours	biodegradation	Not readily biodegradable 2 %

Bis(2,2,6,6-tetramethyl-4-piperidyl) sebacate (52829-07-9)

Method	Exposure time	Value	Results
OECD Test No. 303: Simulation Test - Aerobic Sewage Treatment -- A: Activated Sludge Units; B: Biofilms	28 days	Total organic carbon (TOC)	24 % Moderate

12.3. Bioaccumulative potential

Bioaccumulation

Component Information

Tate Global GmbH

Zum Stadion 4, 63808 Haibach, Germany

T: +49 (0) 6021 63949-0 E: infoDE@tateglobal.com W: tateglobal.com/de

© 2025 Tate Global GmbH
We reserve the right to change specification or design and supply products which may differ from those described and illustrated without notice and without liability.
tate-eco-stützenklebstoff-safety-datasheet-en-de-v2 4/2025

Tate.[®]

ECO-STÜTZENKLEBSTOFF

13

This safety data sheet was created pursuant to the requirements of: Regulation (EC) No. 1907/2006 and Regulation (EC) No. 1272/2008 This SDS is for generic information purposes and does not reflect required country specific information for OEL

Chemical name	Partition coefficient
Trimethoxyvinylsilane	1.1
Dioctyltin oxide	6
Bis(2,2,6,6-tetramethyl-4-piperidyl) sebacate	0.35
Ethyl silicate	3.18

12.4. Mobility in soil

Mobility in soil No information available.

12.5. Results of PBT and vPvB assessment

PBT and vPvB assessment The product does not contain any substance(s) classified as PBT or vPvB above the threshold of declaration.

Chemical name	PBT and vPvB assessment
Trimethoxyvinylsilane	The substance is not PBT / vPvB
Dioctyltin oxide	The substance is not PBT / vPvB
Bis(2,2,6,6-tetramethyl-4-piperidyl) sebacate	The substance is not PBT / vPvB
Ethyl silicate	The substance is not PBT / vPvB PBT assessment does not apply

12.6. Endocrine disrupting properties

Endocrine disrupting properties No information available.

12.7. Other adverse effects

No information available.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Waste from residues/unused products Dispose of contents/container in accordance with local, regional, national, and international regulations as applicable.

Contaminated packaging Handle contaminated packages in the same way as the product itself.
08 04 10 waste adhesives and sealants other than those mentioned in 08 04 09

European Waste Catalogue

Other information Waste codes should be assigned by the user based on the application for which the product was used.

SECTION 14: Transport information

Land transport (ADR/RID)

14.1 UN number or ID number Not regulated
14.2 Proper Shipping Name Not regulated
14.3 Transport hazard class(es) Not regulated
14.4 Packing group Not regulated
14.5 Environmental hazards Not regulated
14.6 Special Provisions None

IMDG

14.1 UN number or ID number 14.2
Proper Shipping Name
14.3 Transport hazard class(es) 14.4
Packing group
14.5 Marine pollutant

14.6 Special Provisions
14.7 Maritime transport in bulk according to IMO instruments

Air transport (ICAO-TI / IATA-DGR) 14.1 UN number or ID number 14.2 Proper Shipping Name
14.3 Transport hazard class(es) 14.4 Packing group

Tate Global GmbH

Zum Stadion 4, 63808 Haibach, Germany
T: +49 (0) 6021 63949-0 E: infoDE@tateglobal.com W: tateglobal.com/de

© 2025 Tate Global GmbH
We reserve the right to change specification or design and supply products which may differ from those described and illustrated without notice and without liability.
tate-eco-stützenklebstoff-safety-datasheet-en-de-v2 4/2025

Tate®

ECO-STÜTZENKLEBSTOFF

This safety data sheet was created pursuant to the requirements of: Regulation (EC) No. 1907/2006 and Regulation (EC) No. 1272/2008 This SDS is for generic information purposes and does not reflect required country specific information for OEL

14.5 Environmental hazards

Not regulated Not regulated Not regulated Not regulated NP

14.6 Special Provisions

None

Not applicable

Not regulated Not regulated Not regulated Not regulated Not applicable None

Section 15: REGULATORY INFORMATION

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

European Union

Registration, Evaluation, Authorization, and Restriction of Chemicals (REACH) Regulation (EC 1907/2006)

SVHC: Substances of Very High Concern for Authorisation:

This product does not contain candidate substances of very high concern at a concentration $\geq 0.1\%$ (Regulation (EC) No. 1907/2006 (REACH), Article 59)

EU-REACH (1907/2006) - Annex XVII - Substances subject to Restriction

This product contains one or more substance(s) subject to restriction (Regulation (EC) No. 1907/2006 (REACH), Annex XVII).

Chemical name	CAS No	Restricted substance per REACH Annex XVII
Dioctyltin oxide	870-08-6	20.

Substance subject to authorisation per REACH Annex XIV

This product does not contain substances subject to authorisation (Regulation (EC) No. 1907/2006 (REACH), Annex XIV)

Export Notification requirements

This product contains substances which are regulated pursuant to Regulation (EC) No. 649/2012 of the European parliament and of the council concerning the export and import of dangerous chemicals

Chemical name	European Export/Import Restrictions per (EC) 689/2008 - Annex Number
Dioctyltin oxide - 870-08-6	I.1

Ozone-depleting substances (ODS) regulation (EC) 1005/2009 Not applicable

Persistent Organic Pollutants Not applicable

National regulations

France

Germany

Ordinance on Industrial Safety and Health - Germany - BetrSichV

No flammable liquids in accordance with BetrSichV

Water hazard class (WGK) TRGS - 510 Storage Class Netherlands

Tate Global GmbH

Zum Stadion 4, 63808 Haibach, Germany

T: +49 (0) 6021 63949-0 E: infoDE@tateglobal.com W: tateglobal.com/de

© 2025 Tate Global GmbH
We reserve the right to change specification or design and supply products which may differ from those described and illustrated without notice and without liability.
tate-eco-stützenklebstoff-safety-datasheet-en-de-v2 4/2025

Tate.[®]

ECO-STÜTZENKLEBSTOFF

This safety data sheet was created pursuant to the requirements of: Regulation (EC) No. 1907/2006 and Regulation (EC) No. 1272/2008 This SDS is for generic information purposes and does not reflect required country specific information for OEL

slightly hazardous to water

(WGK 1) Storage Class 10 : Combustible liquids

List of Carcinogenic, mutagenic and reproductive toxin substances in accordance with Inspectorate SZW (Netherlands)

Not Listed

Denmark

Registration number(s) (P-no.) No information available

Norway

Registration number(s) (PRN-no.) No information available

15.2. Chemical safety assessment

Chemical Safety Assessments have been carried out by the Reach registrants for substances registered at >10 tpa. No Chemical Safety Assessment has been carried out for this mixture.

SECTION 16: Other information

Key or legend to abbreviations and acronyms used in the safety data sheet

Full text of H-Statements referred to under section 3

H226 - Flammable liquid and vapour

H317 - May cause an allergic skin reaction H318 - Causes serious eye damage

H319 - Causes serious eye irritation H332 - Harmful if inhaled

H335 - May cause respiratory irritation H361f - Suspected of damaging fertility H400 - Very toxic to aquatic life

H411 - Toxic to aquatic life with long lasting effects

SVHC: Substances of Very High Concern for Authorisation:

PBT: Persistent, Bioaccumulative, and Toxic (PBT) Chemicals vPvB: Very Persistent and very Bioaccumulative (vPvB) Chemicals STOT RE: Specific target organ toxicity - Repeated exposure

STOT SE: Specific target organ toxicity - Single exposure EWC: European Waste Catalogue

LOW: List of Wastes (see <http://ec.europa.eu/environment/waste/framework/list.htm>)

ADR: European Agreement concerning the International Carriage of Dangerous Goods by Road IATA: International Air Transport Association

ICAO: ICAO-TI: Technical Instructions for the Safe Transport of Dangerous Goods by Air IMDG: International Maritime Dangerous Goods

RID: Regulations concerning the International Carriage of Dangerous Goods by Rail

Legend SECTION 8: Exposure controls/personal protection

TWA
AGW
Ceiling

TWA (time-weighted average)
Occupational exposure limit value
Maximum limit value

ST
EL
BG
W
*

STEL (Short Term Exposure Limit) Biological limit
value
Skin designation

Classification procedure	
Classification according to Regulation (EC) No. 1272/2008 [CLP]	Method Used
Acute oral toxicity	Calculation method
Acute dermal toxicity	Calculation method
Acute inhalation toxicity - gas	Calculation method
Acute inhalation toxicity - Vapour	Calculation method
Acute inhalation toxicity - dust/mist	Calculation method
Skin corrosion/irritation	Calculation method
Serious eye damage/eye irritation	Calculation method
Respiratory sensitisation	Calculation method
Skin sensitisation	On basis of test data
mutagenicity	Calculation method
Carcinogenicity	Calculation method
Reproductive toxicity	Calculation method
STOT - single exposure	Calculation method

Tate Global GmbH

Zum Stadion 4, 63808 Haibach, Germany

T: +49 (0) 6021 63949-0 E: infoDE@tateglobal.com W: tateglobal.com/de

© 2025 Tate Global GmbH

We reserve the right to change specification or design and supply products which may differ from those described and illustrated without notice and without liability.
tate-eco-stützenklebstoff-safety-datasheet-en-de-v2 4/2025

Tate.[®]

ECO-STÜTZENKLEBSTOFF

16

This safety data sheet was created pursuant to the requirements of: Regulation (EC) No. 1907/2006 and Regulation (EC) No. 1272/2008 This SDS is for generic information purposes and does not reflect required country specific information for OEL

STOT - repeated exposure	Calculation method
Acute aquatic toxicity	Calculation method
Chronic aquatic toxicity	Calculation method
Aspiration hazard	Calculation method
Ozone	Calculation method

Key literature references and sources for data used to compile the SDS

European Food Safety Authority (EFSA)

European Chemicals Agency (ECHA) Committee for Risk Assessment (ECHA_RAC) European Chemicals Agency (ECHA) (ECHA_API)

EPA (Environmental Protection Agency) Acute Exposure Guideline Level(s) (AEGl(s))

International Uniform Chemical Information Database (IUCLID) National Institute of Technology and Evaluation (NITE)

NIOSH (National Institute for Occupational Safety and Health)

Organisation for Economic Co-operation and Development Environment, Health, and Safety Publications Organisation for Economic Co-operation and Development High Production Volume Chemicals Programme Organisation for Economic Co-operation and Development Screening Information Data Set

Prepared By Product Safety & Regulatory Affairs

Revision date 23-Jan-2023

Revision note Training SDS sections updated
Advice Further No information available
information No information available

Safety Data Sheet according to Regulation (EC) No. 1907/2006 (REACH) Disclaimer

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

Tate Global GmbH

Zum Stadion 4, 63808 Haibach, Germany

T: +49 (0) 6021 63949-0 E: infoDE@tateglobal.com W: tateglobal.com/de

© 2025 Tate Global GmbH
We reserve the right to change specification or design and supply products which may differ from the described and illustrated without notice and without liability.
tate-eco-stützenklebstoff-safety-datasheet-en-de-v2 4/2025

Tate.[®]

Tate.®

Tate Global GmbH

Zum Stadion 4, 63808 Haibach, Germany

T: +49 (0) 6021 63949-0 E: infoDE@tateglobal.com W: tateglobal.com/de

© 2025 Tate Global GmbH

We reserve the right to change specification or design and supply products which may differ from those described and illustrated without notice and without liability.
tate-eco-stützenklebstoff-safety-datasheet-en-de-v2 4/2025

Tate.®