

PEDESTAL SPECIFICATIONS

Pedestal Assembly

- Assembly from 2-7/8" (73 mm) to 4" (102 mm) FFH shall provide a 6,000 lb. (2722 kg) axial load without permanent deformation.
- Assembly shall provide $\pm 1/2"$ (12.5 mm) total adjustment with a minimum finished floor height of 2-7/8" (73 mm).
- Overturning moment of 1,000 in./lbs. (5,600 cm/kgs) when Tate recommended pedestal adhesive is utilized.
- All pedestal components and fasteners are completely electro zinc free.
- Zinc electroplating shall be prohibited on all pedestal components and fasteners.

Pedestal Head


- Die formed steel pedestal head with threaded core for height adjustment. Head and installed 2' (60 cm) stringers shall provide full perimeter edge support for panel.
- Threaded core shall be 3/4" - 10 UNC.
- Pedestal head shall have tapped holes for engagement of stringer fasteners.
- Stringers shall be attached with 1/4" - 20 flat-head screws.

Pedestal Base

- Base to be at least 16" (103 cm) square and galvanized steel.
- Solid steel stud shall be 3/4" - 10 UNC and projection welded to base plate.

Stringers

- Heavy duty roll formed steel stringer shall be 1-1/4" (31.75 mm) deep X 3/4" (19 mm) wide and shall withstand 450 lb. (204 kg) mid-span load.
- Galvanized stringer construction to prevent corrosion. Zinc electroplating is prohibited.
- Stringer grid pattern shall be 60cm / 60cm only.



Perimeter

- Perimeter pedestal shall provide support for panels around columns, at walls, curbs and fascia.



Tate reserves the right to amend product information without prior notice. Care has been taken to ensure that the contents of this publication are accurate, but Tate, its parent company and its subsidiary companies do not accept responsibility for errors or information that is found to be misleading or outdated. Suggestions for, or descriptions of, technical specifications and the end user or application of products are provided and must be verified prior to use. To ensure you are viewing the most recent and accurate product information, please scan the QR code.